



Resin consumption for Brawo AC, HT & TC

Date: 2019-06-04

	AC	HT	TC	AC	HT	TC	AC	HT	TC	AC	HT	TC	AC	HT	TC			
Article	BRAWOLINER® + HT			DN 70			DN 100			DN 125			DN 150			DN 200/250		
Resin consumption BRAWO AC, HT, TC per linear meter:	0,8 kg	0,9 kg	0,9 kg	1,1 kg	1,3 kg	1,2 kg	1,4 kg	1,6 kg	1,5 kg	1,7 kg	2,0 kg	1,8 kg	2,3 kg	2,7 kg	2,4 kg			
Resin consumption all resins in Litre per linear meter:	0,73 l			1,0 l			1,27 l			1,55 l			2,09 l					
Roller distance of the impregnation plant:	8,5 mm			8,5 mm			8,5 mm			8,5 mm			8,5 mm					
Article	BRAWOLINER® XT + HT						DN 125			DN 150			DN 200/250					
Resin consumption BRAWO AC, HT, TC per linear meter:				2,0 kg			2,1 kg			2,3 kg			2,4 kg			3,1 kg		3,3 kg
Resin consumption all resins in Litre per linear meter:							1,83 l			2,14 l			2,98 l					
Roller distance of the impregnation plant:							11 mm			11 mm			11 mm					
Article	BRAWOLINER® 2D + HT						DN 70 - 100											
Resin consumption BRAWO AC, HT, TC per linear meter:				0,9 kg			1,1 kg			1,0 kg								
Resin consumption all resins in Litre per linear meter:							0,73 l											
Roller distance of the impregnation plant:							10 mm											
Article	BRAWOLINER® 3D DN 100-150 + HT						DN 100 - 150											
Resin consumption BRAWO AC, HT, TC per linear meter:				1,5 kg			1,8 kg			1,6 kg								
Resin consumption all resins in Litre per linear meter:							1,36 l											
Roller distance of the impregnation plant:							12 mm											
Article	BRAWOLINER® 4D + HT						DN 150 - 225											
Resin consumption BRAWO AC, HT, TC per linear meter:				2,3 kg			2,7 kg			2,4 kg								
Resin consumption all resins in Litre per linear meter:							2,09 l											
Roller distance of the impregnation plant:							12 mm											
Article	BRAWOLINER® 3D DN 300-400						DN 300 - 400											
Resin consumption BRAWO AC, HT, TC per linear meter:				6,5 kg			6,9 kg											
Resin consumption all resins in Litre per linear meter:							5,91 l											
Roller distance of the impregnation plant:							15,5 mm											
Article	BRAWOLINER® 50 Special + HT						DN 50 - 70											
Resin consumption BRAWO AC, HT, TC per linear meter:				0,5 kg			0,6 kg			0,5 kg								
Resin consumption all resins in Litre per linear meter:							0,46 l											
Roller distance of the impregnation plant:							7 mm											