

| ARTICLE                                                                | HOUSELINER FL 2.5 mm | DN 30-50  | DN 40-60  | DN 45-70  | DN 50-70  | DN 63-75  | DN 70-100  | DN 90-125  | DN 100-150 | DN 110-160 |            |            |
|------------------------------------------------------------------------|----------------------|-----------|-----------|-----------|-----------|-----------|------------|------------|------------|------------|------------|------------|
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      | 0.176 lbs | 0.233 lbs | 0.268 lbs | 0.268 lbs | 0.367 lbs | 0.409 lbs  | 0.515 lbs  | 0.557 lbs  | 0.621 lbs  |            |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      | 0.188 lbs | 0.248 lbs | 0.286 lbs | 0.286 lbs | 0.391 lbs | 0.437 lbs  | 0.549 lbs  | 0.595 lbs  | 0.662 lbs  |            |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      | 0.2165 in | 0.2165 in | 0.2165 in | 0.2165 in | 0.2165 in | 0.2165 in  | 0.2165 in  | 0.2165 in  | 0.2165 in  |            |            |
| ARTICLE                                                                | HOUSELINER FL 3 mm   | DN 30-50  | DN 45-70  | DN 50-70  | DN 60-75  | DN 63-75  | DN 63-100  | DN 70-100  | DN 90-125  | DN 100-120 | DN 100-150 |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      | 0.198 lbs | 0.325 lbs | 0.318 lbs | 0.367 lbs | 0.381 lbs | 0.409 lbs  | 0.473 lbs  | 0.614 lbs  | 0.677 lbs  | 0.677 lbs  |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      | 0.211 lbs | 0.346 lbs | 0.339 lbs | 0.391 lbs | 0.406 lbs | 0.437 lbs  | 0.504 lbs  | 0.655 lbs  | 0.723 lbs  | 0.723 lbs  |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      | 0.2559 in | 0.2559 in | 0.2559 in | 0.2559 in | 0.2559 in | 0.2559 in  | 0.2559 in  | 0.2559 in  | 0.2559 in  | 0.2559 in  |            |
| ARTICLE                                                                | HOUSELINER FL 4 mm   |           |           |           |           | DN 63-100 | DN 70-100  | DN 80-110  | DN 90-125  | DN 100-150 | DN 120-150 | DN 150-225 |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           |           | 0.557 lbs | 0.621 lbs  | 0.734 lbs  | 0.776 lbs  | 0.882 lbs  | 1.030 lbs  | 1.355 lbs  |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           |           | 0.595 lbs | 0.662 lbs  | 0.783 lbs  | 0.828 lbs  | 0.941 lbs  | 1.099 lbs  | 1.445 lbs  |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           |           | 0.3346 in | 0.3346 in  | 0.3346 in  | 0.3346 in  | 0.3346 in  | 0.3346 in  | 0.3346 in  |
| ARTICLE                                                                | HOUSELINER FL 5 mm   |           |           |           |           |           | DN 150-225 | DN 200-250 | DN 225-300 | DN 250-300 | DN 300-400 |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           |           |           | 1.355 lbs  | 2.173 lbs  | 2.589 lbs  | 2.879 lbs  | 3.373 lbs  |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           |           |           | 1.445 lbs  | 2.318 lbs  | 2.762 lbs  | 3.071 lbs  | 3.597 lbs  |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           |           |           | 0.4134 in  | 0.4134 in  | 0.4134 in  | 0.4134 in  | 0.4134 in  |            |
| ARTICLE                                                                | HOUSELINER FIX 3 mm  |           |           |           |           |           | DN 75      | DN 100     | DN 150     |            |            |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           |           |           | 0.445 lbs  | 0.557 lbs  | 0.882 lbs  |            |            |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           |           |           | 0.474 lbs  | 0.595 lbs  | 0.941 lbs  |            |            |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           |           |           | 0.2559 in  | 0.2559 in  | 0.2559 in  |            |            |            |
| ARTICLE                                                                | HOUSELINER FIX 4 mm  |           |           |           |           |           |            | DN 100     | DN 150     | DN 225     |            |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           |           |           |            | 0.917 lbs  | 1.291 lbs  | 1.969 lbs  |            |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           |           |           |            | 0.978 lbs  | 1.377 lbs  | 2.100 lbs  |            |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           |           |           |            | 0.3346 in  | 0.3346 in  | 0.3346 in  |            |            |
| ARTICLE                                                                | HOUSELINER FIX 5 mm  |           |           |           |           |           |            |            | DN 150     | DN 225     |            |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           |           |           |            |            | 1.665 lbs  | 1.776 lbs  |            |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           |           |           |            |            | 2.413 lbs  | 2.574 lbs  |            |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           |           |           |            |            | 0.4134 in  | 0.4134 in  |            |            |
| ARTICLE                                                                | HOUSELINER FLT       |           |           |           | DN 50-70  | DN 60-90  | DN 70-100  | DN 90-125  | DN 100-150 |            |            |            |
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                      |           |           |           | 0.282 lbs | 0.339 lbs | 0.409 lbs  | 0.522 lbs  | 0.543 lbs  |            |            |            |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                      |           |           |           | 0.301 lbs | 0.361 lbs | 0.437 lbs  | 0.557 lbs  | 0.580 lbs  |            |            |            |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                      |           |           |           | 0.2756 in | 0.2756 in | 0.2756 in  | 0.2756 in  | 0.2756 in  |            |            |            |



| ARTICLE                                                                | HOUSELINER FLF WO | DN 50-70  | DN 70-100 | DN 100-150 | DN 150-225 |
|------------------------------------------------------------------------|-------------------|-----------|-----------|------------|------------|
| RESIN CONSUMPTION ULTRA, FAST, MEDIUM, SLOW & HOT CURE PER LINER FEET: |                   | 0.212 lbs | 0.494 lbs | 0.776 lbs  | 1.552 lbs  |
| RESIN CONSUMPTION UVLCR, MA+ & MA-HR PER LINER FEET:                   |                   | 0.226 lbs | 0.527 lbs | 0.828 lbs  | 1.656 lbs  |
| ROLLER DISTANCE OF THE IMPREGNATION PLANT:                             |                   | 0.2756 in | 0.3937 in | 0.4331 in  | 0.4724 in  |