

# **ULTRA HARDENER**

Revision date: 03/03/2022 Version: 1.0.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: ULTRA HARDENER

Unique Formula Identifier (UFI): TDCM-T3EH-J00W-5X2K

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended uses:** Hardener for epoxy resin.

# 1.3. Details of the supplier of the safety data sheet

**Supplier** 

Company: SACPRO AB
Address: Källviksvägen 10

 Zip code:
 791 52

 City:
 Falun

 Country:
 SWEDEN

 E-mail:
 info@sacpro.se

 Phone:
 +46 23 79 06 50

#### 1.4. Emergency Telephone Number

Members of the public: 111 (NHS 111 (Scotland: NHS 24)).

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

**CLP-classification:** Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 Aquatic Chronic 2;H411

Most serious harmful effects: Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic

skin reaction. Toxic to aquatic life with long lasting effects.

## 2.2. Label elements

### **Pictograms**



Signal word: Danger

Contains

**Substance:** Phenol, styrenated; 1,3-Benzenedimethanamine; bicyklo[2.2.1]heptanebis(metylamine);

3,6-diazaoktan-1,8-diamin;

H-phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.



#### **ULTRA HARDENER**

Revision date: 03/03/2022

Version: 1.0.0

H411 Toxic to aquatic life with long lasting effects.

P-phrases

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+361+353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P501 Dispose of contents/container in accordance with local regulation.

#### 2.3. Other hazards

When mixing two components, consult the safety data sheets for both components.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

| Substance                                    | CAS No./ EC No./<br>REACH Reg. No.          | Concentration | Notes | CLP-classification  |
|--|---|---------------|-------|---|
| Phenol, styrenated                           | 61788-44-1<br>262-975-0<br>01-2119980970-27 | 30 - 60%      |       | Skin Irrit. 2;H315<br>Skin Sens. 1;H317<br>Aquatic Chronic 2;H411   |
| bicyklo[2.2.<br>1]heptanebis<br>(metylamine) | 56602-77-8<br>260-280-7                     | 10 - 30%      |       | Acute Tox. 4;H302<br>Skin Corr. 1C;H314<br>Aquatic Chronic 3;H412   |
| 1,3-<br>Benzenedimethanamine                 | 1477-55-0<br>216-032-5                      | 10 - 30%      |       | Acute Tox. 4;H302<br>Skin Corr. 18;H314<br>Skin Sens. 1;H317<br>Acute Tox. 4;H332<br>Aquatic Chronic 3;H412 |
| 3,6-diazaoktan-1,8-<br>diamin                | 90640-67-8<br>203-950-6<br>01-2119487919-13 | 5 - 10%       |       | Acute Tox. 4;H302<br>Acute Tox. 4;H312<br>Skin Corr. 1B;H314<br>Skin Sens. 1;H317<br>Aquatic Chronic 3;H412 |

Please see section 16 for the full text of H- / EUH-phrases..

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

**Inhalation:** Seek fresh air. Seek medical advice in case of persistent discomfort.

Ingestion: Wash out mouth thoroughly and drink 1-2 glasses of water in small sips. Do not induce

vomiting. Seek medical advice immediately.

**Skin contact:** Wash skin with soap and water. Do not use organic solvents. Take off contaminated

clothing and wash before reuse. Seek medical advice in case of persistent discomfort.

Organic solvents.

**Eye contact:** Open eye wide, remove any contact lenses and flush immediately with water (preferably

using eye wash equipment). Seek medical advice immediately. Continue flushing until

medical attention is obtained.

**General:** Running water and eye wash equipment must be available.



#### **ULTRA HARDENER**

Revision date: 03/03/2022

Version: 1.0.0

#### 4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes. The product is corrosive. May cause sensitisation by skin contact.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Open eye wide, remove any contact lenses and flush immediately with water (preferably using eye wash equipment). Seek medical advice immediately. Continue flushing until medical attention is obtained.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media: Extinguish with powder, foam, carbon dioxide or water mist.

Unsuitable extinguishing

media:

Do not use water stream, as it may spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Not flammable, but combustible. Hazardous fumes are formed in fire conditions. Nitrous gases/ Carbon monoxide and carbon dioxide.

#### 5.3. Advice for firefighters

If there is a risk of exposure to vapour and flue gases, a self-contained breathing apparatus must be worn.

Other Information: Notify proper authorities in case of contamination of soil or aquatic environment or

discharge to drains.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep unnecessary people away, isolate hazard area and deny entry. Wear suitable

protective clothing. Wear safety goggles if there is a risk of eye splash.

#### 6.2. Environmental precautions

Prevent spillage from entering drains and/or surface water. Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

#### 6.3. Methods and material for containment and cleaning up

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers.

#### 6.4. Reference to other sections

See section 8 for type of protective equipment. See section 7 for handling and storage. See section 13 for instructions on disposal.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Running water and eye wash equipment must be available. Put lids on containers immediately after use. Avoid contact with skin and eyes. All work must be carried out under well-ventilated conditions. Wash hands before breaks, before using restroom facilities, and at the end of work. Do not eat, drink or smoke during work.

#### 7.2. Conditions for safe storage, including any incompatibilities



#### **ULTRA HARDENER**

Revision date: 03/03/2022 Version: 1.0.0

Keep in tightly closed original packaging. Store in a dry, cool, well-ventilated area.

# 7.3. Specific end use(s)

Polymerise together with part A during heat emission. The product is corrosive. May cause an allergic skin reaction.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limit: Contains no substances subject to reporting requirements

Legal basis: None known.

#### 8.2. Exposure controls

Personal protective equipment, Wear safety goggles/face protection. Eye protection must conform to EN 166. eye/face protection:

Personal protective equipment, Wear suitable protective clothing. skin protection:

hand protection:

Personal protective equipment, Wear gloves. Type of material: Nitrile rubber/ Butyl rubber. Penetration time of glove material: 3 hours. We have reduced the penetration time by a factor of 3, when the test standard EN 374-3 is done at 23°C, while the temperature inside the glove is approx. 35°C.In addition, the elastic material extends during use, thereby glove thickness and penetration time is reduced. Recommended thickness of the glove is ≥ 0.4 mm. Selection of the suitable gloves does not only depend on the material, but also on quality and these will vary between manufacturers.

respiratory protection:

Personal protective equipment, In case of insufficient ventilation, wear respiratory protective equipment. Filter type: A

Other Information: Wash hands before breaks, before using restroom facilities, and at the end of work. Take

off contaminated clothing and wash before reuse.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

| Parameter  | Value/unit                                     |
|------------|--|
| State      | Liquid   |
| Colour     | Yellowish brown                                |
| Odour      | Amine odour                                    |
| Solubility | Miscible with the following: Organic solvents. |

| Parameter                               | Value/unit | Remarks |
|---|------------|---------|
| Odour threshold                         | No data    |         |
| Melting point                           | No data    |         |
| Freezing point                          | No data    |         |
| Initial boiling point and boiling range | > 150 °C   | 760mmHg |
| Flammability (solid, gas)               | No data    |         |
| Flammability limits                     | No data    |         |
| Explosion limits                        | No data    |         |
| Flash Point                             | > 150 °C   |         |
| Auto-ignition temperature               | > 150 °C   |         |
| Decomposition temperature               | No data    |         |
| pH (solution for use)                   | No data    |         |
| pH (concentrate)                        | No data    |         |



# **ULTRA HARDENER**

Revision date: 03/03/2022

|                       | VC131011. 1.0.0   |
|-----------------------|---|
| No data               |   |
| 0.3 Pas               | 25°C  |
| No data               |   |
| No data               |   |
| 1,0 g/cm <sup>3</sup> | 20°C  |
| No data               |   |
|                       | 0.3 Pas No data No data 1,0 g/cm³ No data No data No data |

#### 9.2. Other information

Parameter Value/unit Remarks

Other Information: Solubility in water: Insoluble

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

# 10.2. Chemical stability

The product is stable when used in accordance with the supplier's directions.

#### 10.3. Possibility of hazardous reactions

Reacts under heat generation with the following: Epoxy.

# 10.4. Conditions to avoid

Avoid contact with the following: Oxidisers/ Strong acids.

#### 10.5. Incompatible materials

Organic peroxides.

#### 10.6. Hazardous decomposition products

Hazardous fumes are formed in fire conditions. Nitrous gases/ Carbon monoxide and carbon dioxide.

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity - oral

# Phenol, styrenated, cas-no 61788-44-1

| Organism | Test Type | Exposure time | Value       | Conclusion | Test method | Source |
|----------|-----------|---------------|-------------|------------|-------------|--------|
| Rat      | LD50      |               | > 2000mg/kg |            |             |        |

# 1,3-Benzenedimethanamine, cas-no 1477-55-0

| Organism | Test Type | Exposure time | Value     | Conclusion | Test method | Source |
|----------|-----------|---------------|-----------|------------|-------------|--------|
| Rat      | LD50      |               | 930 mg/kg |            |             |        |

#### bicyklo[2.2.1]heptanebis(metylamine), cas-no 56602-77-8

| Organism | Test Type | Exposure time | Value     | Conclusion | Test method | Source |
|----------|-----------|---------------|-----------|------------|-------------|--------|
| Rat      | LD50      |               | 961 mg/kg |            |             |        |

# 3,6-diazaoktan-1,8-diamin, cas-no 90640-67-8

| Organism | Test Type | Exposure time | Value           | Conclusion | Test method | Source |
|----------|-----------|---------------|-----------------|------------|-------------|--------|
| Rat      | LD50      |               | 300 - 2000mg/kg |            |             |        |



#### **ULTRA HARDENER**

Revision date: 03/03/2022

Version: 1.0.0

Ingestion may cause caustic burning in mouth, aesophagus and stomach.

### Acute toxicity - dermal

#### 1,3-Benzenedimethanamine, cas-no 1477-55-0

| Organism | Test Type Exposure time |  | Value       | Conclusion | Test method | Source |
|----------|-------------------------|--|-------------|------------|-------------|--------|
| Rabbit   | LD50                    |  | > 3100mg/kg |            |             |        |

#### 3,6-diazaoktan-1,8-diamin, cas-no 90640-67-8

| Organism | Test Type | Exposure time | Value               | Conclusion | Test method | Source |
|----------|-----------|---------------|---------------------|------------|-------------|--------|
| Rabbit   | LD50      |               | 1000 -<br>2000mg/kg |            |             |        |

Skin contact may cause irritation, redness and burns. Prolonged or repeated skin contact may cause allergic eczema.

#### Acute toxicity - inhalation

#### 1,3-Benzenedimethanamine, cas-no 1477-55-0

| Organism | Test Type | Exposure time | Value     | Conclusion | Test method | Source |
|----------|-----------|---------------|-----------|------------|-------------|--------|
| Rat      | LC50      | 4h            | 1.34 mg/l |            |             |        |

The amines in the hardener have a very low vapour pressure, but inhalation of high concentrations may cause irritation of mucous membranes, headache and nausea.

**Skin corrosion/irritation:** The product is corrosive.

Serious eye damage/eye

irritation:

Eye contact may result in deep caustic burns, pain, tearing and cramping of the eyelids.

Risk of serious eye injury and loss of sight.

Respiratory sensitisation or

skin sensitisation:

May cause reddening and sensitization or other allergic responce.

### 11.2. Information on other hazards

Endocrine disrupting

properties:

None known.

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

# Phenol, styrenated, cas-no 61788-44-1

| Organism  | Species | Exposure time | Test Type | Value      | Conclusion | Test method | Source |
|-----------|---------|---------------|-----------|------------|------------|-------------|--------|
| Crustacea |         | 48h           | EC50      | 1 - 10mg/l |            |             |        |
| Algae     |         | 72h           | EC50      | 3.14 mg/l  |            |             |        |
| Fish      |         | 96h           | LC50      | 14.8 mg/l  |            |             |        |

# 1,3-Benzenedimethanamine, cas-no 1477-55-0

| Organism  | Species        | Exposure time | Test Type | Value     | Conclusion | Test method | Source |
|-----------|----------------|---------------|-----------|-----------|------------|-------------|--------|
| Crustacea |                | 48h           | EC50      | 15.2 mg/l |            |             |        |
| Algae     |                | 72h           | EC50      | 20.3 mg/l |            |             |        |
| Fish      | Leuciscus idus | 96h           | LC50      | 87.6 mg/l |            |             |        |

### bicyklo[2.2.1]heptanebis(metylamine), cas-no 56602-77-8

| Organism  | Species          | Exposure time | Test Type | Value   | Conclusion | Test method | Source |
|-----------|------------------|---------------|-----------|---------|------------|-------------|--------|
| Crustacea | Daphnia<br>magna | 48h           | EC50      | 31 mg/l |            |             |        |
| Algae     |                  | 72h           |           | 35 mg/l |            |             |        |

#### 3,6-diazaoktan-1,8-diamin, cas-no 90640-67-8

|  |  | Organism | Species | Exposure time | Test Type | Value | Conclusion | Test method | Source |
|--|--|----------|---------|---------------|-----------|-------|------------|-------------|--------|
|--|--|----------|---------|---------------|-----------|-------|------------|-------------|--------|



#### **ULTRA HARDENER**

Revision date: 03/03/2022 Version: 1.0.0

Fish 96h EC50 > 100mg/l Crustacea 48h EC50 10 - 100mg/l

No results from ecotoxicological tests are available. Ecotoxicological information only related to components.

#### 12.2. Persistence and degradability

Not readily biodegradable.

#### 12.3. Bioaccumulative potential

Test data are not available.

#### 12.4. Mobility in soil

Test data are not available.

#### 12.5. Results of PBT and vPvB assessment

Not applicable

# 12.6. Endocrine disrupting properties

None known.

#### 12.7. Other adverse effects

May change the pH of the water. Harmful to aquatic life with long lasting effects.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Destruction according to local regulations.

Disposal methods: May be disposed of by mixing with the right amount of epoxy-resin.

Contaminated packaging: Put the empty container up-side-down. Use a tool to completely empty the container. Sort the waste according to local regulations.

Category of waste: 08 01 11\* waste paint and varnish containing organic solvents or other hazardous

substances

15 01 10\* packaging containing residues of or contaminated by hazardous substances

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number or ID number:** 3267

14.2. UN proper shipping

name:

CORROSIVE LIQUID. BASIC, ORGANIC, N.O.S.

(1,3-

Benzenedimethanamine)

14.4. Packing group:

hazards:

14.5. Environmental

The product should not be

labelled as an

Ш

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

8

Hazard label(s): 8

Hazard identification number: **Tunnel restriction code:** Ε

Inland water ways transport (ADN)

14.1. UN number or ID number: 3267 14.4. Packing group: Ш

7/9



### **ULTRA HARDENER**

Revision date: 03/03/2022

Version: 1.0.0

14.2. UN proper shipping

name:

CORROSIVE LIQUID. BASIC, ORGANIC, N.O.S.

(1,3-Benzenedimethanamine) hazards:

14.5. Environmental The product should not be

labelled as an

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

Transport in tank vessels:

8

Hazard label(s):

Sea transport (IMDG)

14.1. UN number or ID number: 14.2. UN proper shipping

name:

3267 CORROSIVE LIQUID,

BASIC, ORGANIC, N.O.S.

(1,3-

Benzenedimethanamine)

14.3. Transport hazard

class(es):

Hazard label(s): EmS:

8

F-A, S-B

14.4. Packing group:

14.5. Environmental

hazards:

The product is not a Marine

Pollutant (MP).

**Environmental Hazardous** 

Substance Name(s):

**IMDG** Code segregation

group:

Segr. grp. 18 - Alkalis

(SGG18)

Air transport (ICAO-TI / IATA-DGR)

14.1. UN number or ID number: 3267

14.2. UN proper shipping name:

CORROSIVE LIQUID. BASIC, ORGANIC, N.O.S.

(1,3-

Benzenedimethanamine)

14.4. Packing group:

14.5. Environmental

hazards:

Ш The product should not be

labelled as an

environmental hazard (symbol: fish and tree).

14.3. Transport hazard

class(es):

Hazard label(s): R

14.6. Special precautions for user

14.7. Maritime transport in bulk according to IMO instruments

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Special Provisions:** This product is assessed and classified in accordance with the requirements of the

European Parliament and Council Regulation (EC) No 1272/2008 and subsequent

amendments.

# 15.2. Chemical Safety Assessment

# **SECTION 16: Other information**

#### Version history and indication of changes

| Version | Revision date | Responsible | Changes  |
|---------|---------------|-------------|----------|
| 1.0.0   | 03/03/2022    | SACPRO AB   | Approved |

Abbreviations: ADR: Accord européen sur le transport des marchandises dangereuses par Route

> (European Agreement concerning the International Carriage of Dangerous Goods by Road)RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)IMDG: International Maritime Code for Dangerous GoodsIATA: International Air Transport AssociationIATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)ICAO: International Civil Aviation

OrganizationICAO-TI: Technical Instructions by the "International Civil Aviation

8/9



# **ULTRA HARDENER**

Revision date: 03/03/2022

Version: 1.0.0

Organization" (ICAO)GHS: Globally Harmonized System of Classification and Labelling of

ChemicalsEINECS: European Inventory of Existing Commercial Chemical SubstancesCAS: Chemical Abstracts Service (division of the American Chemical

Society)DNEL: Derived No-Effect Level (REACH)PNEC: Predicted No-Effect Concentration

(REACH)LC50: Lethal concentration, 50 percentLD50: Lethal dose, 50 percent

Other Information: The information contained herein is based on the best of our knowledge and shall describe

our product under the aspect of safety. They are not meant to guarantee specific properties of the product. Recipients of our product must take responsibility for observing existing

laws and regulations.

**Classification method:** Calculation based on the hazards of the known components.

#### **List of relevant H-statements**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

#### SDS is prepared by

Company: SACPRO AB
Address: Källviksvägen 10

 Zip code:
 791 52

 City:
 Falun

 Country:
 SWEDEN

 E-mail:
 info@sacpro.se

 Phone:
 +46 23 79 06 50

Document language: GB